Stainless steel apparatus castors

Description
Fork of stainless steel
dual-row ball bearings collar in fork head

Model
- Swivel castor
- Fixed castor
- Swivel castor with total brake

40 - 100 kg

INOX

mm	mm	kg	mm	mm	mm	mm	mm			
50	18	40	70	60x60	45x45	6,5	26	G100.A80.051	G110.A80.051	G120.A80.051
75	24	60	101	60x60	45x45	6,5	25	G100.A80.076	G110.A80.076	G120.A80.076
100	28	60	136	76x70	60x50	8,3	35	G100.A80.100	G110.A80.100	G120.A80.100
125	28	70	158	76x70	60x50	8,3	35	G100.A80.126	G110.A80.126	G120.A80.126

Tread
Grey rubber

Wheel body
Plastic

Bearing
Plain bearing

mm	mm	kg	mm	mm	mm	mm	mm			
50	18	55	70	60x60	45x45	6,5	26	G100.A90.051	G110.A90.051	G120.A90.051
75	23	60	101	60x60	45x45	6,5	25	G100.A90.076	G110.A90.076	G120.A90.076
100	27	90	136	76x70	60x50	8,3	35	G100.A90.100	G110.A90.100	G120.A90.100
120	27	100	156	76x70	60x50	8,3	35	G100.A90.120	G110.A90.120	G120.A90.120

Tread
Plastic

Wheel body
Plastic

Bearing
Plain bearing

Stainless steel apparatus castors

Description
Fork of stainless steel
dual-row ball bearings collar in fork head

Model
- Swivel castor
- Swivel castor with total brake

INOX

40 - 100 kg

mm	mm	kg	mm	mm	mm				
50	18	40	70	12	26			G101.A80.051	G121.A80.051
75	24	60	101	12	25			G101.A80.076	G121.A80.076
100	28	60	134	12	35			G101.A80.100	G121.A80.100
125	28	70	156	12	35			G101.A80.126	G121.A80.126

Tread
Grey rubber

Wheel body
Plastic

Bearing
Plain bearing

mm	mm	kg	mm	mm	mm				
50	18	55	70	12	26			G101.A90.051	G121.A90.051
75	23	60	101	12	25			G101.A90.076	G121.A90.076
100	27	90	134	12	35			G101.A90.100	G121.A90.100
120	27	100	156	12	35			G101.A90.120	G121.A90.120

Tread
Plastic

Wheel body
Plastic

Bearing
Plain bearing

Stainless steel transport castors

Description
Fork of stainless steel
dual-row ball bearings collar in fork head

Model
- Swivel castor
- Fixed castor
- Swivel castor with total brake

60 - 300 kg

INOX

mm	mm	kg	mm	mm	mm	mm	mm			
80	30	100	108	95x80	80x60	9	32	H100.A90.080	H110.A90.080	H120.A90.080
100	30	130	127	95x80	80x60	9	32	H100.A90.100	H110.A90.100	H120.A90.100
125	37,5	130	155	95x80	80x60	9	32	H100.A90.125	H110.A90.125	H120.A90.125
150	40	300	192	129x106	105x80	11	52	H100.A90.150	H110.A90.150	H120.A90.150
200	50	300	240	129x106	105x80	11	48	H100.A90.200	H110.A90.200	H120.A90.200

Tread
Plastic

Wheel body
Plastic

Bearing
Plain bearing

80	30	60	108	95x80	80x60	9	32	H100.B43.080	H110.B43.080	H120.B43.080
100	30	80	127	95x80	80x60	9	32	H100.B43.100	H110.B43.100	H120.B43.100
125	35	100	155	95x80	80x60	9	32	H100.B43.125	H110.B43.125	H120.B43.125
150	40	140	192	129x106	105x80	11	52	H100.B43.150	H110.B43.150	H120.B43.150
200	50	200	240	129x106	105x80	11	48	H100.B43.200	H110.B43.200	H120.B43.200

Tread
Thermopl. tyre, grey

Wheel body
Plastic

Bearing
Plain bearing

80	28	100	108	95x80	80x60	9	32	H100.B26.080	H110.B26.080	H120.B26.080
100	30	130	127	95x80	80x60	9	32	H100.B26.100	H110.B26.100	H120.B26.100
125	32	130	155	95x80	80x60	9	32	H100.B26.125	H110.B26.125	H120.B26.125
150	35	200	192	129x106	105x80	11	52	H100.B26.150	H110.B26.150	H120.B26.150
200	45	200	240	129x106	105x80	11	48	H100.B26.200	H110.B26.200	H120.B26.200

Tread
Polyurethane, red
98+/-4 Shore A

Wheel body
Plastic

Bearing
Plain bearing

80	28	70	108	95x80	80x60	9	32	H100.B32.080	H110.B32.080	H120.B32.080
100	32	110	127	95x80	80x60	9	32	H100.B32.100	H110.B32.100	H120.B32.100
125	39	130	155	95x80	80x60	9	32	H100.B32.125	H110.B32.125	H120.B32.125
150	40	200	192	129x106	105x80	11	52	H100.B32.150	H110.B32.150	H120.B32.150
200	50	200	240	129x106	105x80	11	48	H100.B32.200	H110.B32.200	H120.B32.200

Tread
Polyurethane, blue
85+/-4 Shore A

Wheel body
Plastic

Bearing
Plain bearing

Stainless steel transport castors

BS ROLLEN®
we are moving everything

Description
Fork of stainless steel
dual-row ball bearings collar in fork head

Model
- Swivel castor
- Swivel castor with total brake

INOX

60 - 200 kg

mm	mm	kg	mm	mm	mm				
80	30	100	108	12,2	32			H101.A90.080	H121.A90.080
100	30	130	127	12,2	32			H101.A90.100	H121.A90.100
125	34	130	160	12,2	47			H101.A90.125	H121.A90.125
150	44	200	192	12,2	52			H101.A90.150	H121.A90.150
200	50	200	240	12,2	48			H101.A90.200	H121.A90.200

Tread
Plastic

Wheel body
Plastic

Bearing
Plain bearing

80	30	60	108	12,2	32			H101.B43.080	H121.B43.080
100	30	80	127	12,2	32			H101.B43.100	H121.B43.100
125	35	100	160	12,2	47			H101.B43.125	H121.B43.125
150	40	140	192	12,2	52			H101.B43.150	H121.B43.150
200	50	200	240	12,2	48			H101.B43.200	H121.B43.200

Tread
Thermopl. tyre, grey

Wheel body
Plastic

Bearing
Plain bearing

80	28	100	108	12,2	32			H101.B26.080	H121.B26.080
100	30	130	127	12,2	32			H101.B26.100	H121.B26.100
125	32	130	160	12,2	47			H101.B26.125	H121.B26.125
150	35	200	192	12,2	52			H101.B26.150	H121.B26.150
200	45	200	240	12,2	48			H101.B26.200	H121.B26.200

Tread
Polyurethane, red
98+/-4 Shore A

Wheel body
Plastic

Bearing
Plain bearing

80	28	70	108	12,2	32			H101.B32.080	H121.B32.080
100	32	110	127	12,2	32			H101.B32.100	H121.B32.100
125	39	130	160	12,2	47			H101.B32.125	H121.B32.125
150	40	200	192	12,2	52			H101.B32.150	H121.B32.150
200	50	200	240	12,2	48			H101.B32.200	H121.B32.200

Tread
Polyurethane, blue
85+/-4 Shore A

Wheel body
Plastic

Bearing
Plain bearing

Stainless steel heavy duty castors

Description
Fork of stainless steel
dual-row ball bearings collar in fork head

Model
- Swivel castor
- Fixed castor
- Swivel castor with total brake

300 - 700 kg

INOX

mm	mm	kg	mm	mm	mm	mm	mm			
100	40	300	128	100x84	80x60	9	42	HS100.B28.100	HS110.B28.100	HS120.B28.100
125	40	300	157	100x84	80x60	9	53	HS100.B28.125	HS110.B28.125	HS120.B28.125
125	45	500	164	132x110	105x80	12	61	HS100.B28.126	HS110.B28.126	HS120.B28.126
150	45	600	195	132x110	105x80	12	62	HS100.B28.150	HS110.B28.150	HS120.B28.150
200	50	700	242	132x110	105x80	12	61	HS100.B28.200	HS110.B28.200	HS120.B28.200

Available alternative: Plain bearing

Tread
Polyurethane, red
98+/-4 Shore A

Wheel body
Plastic

Bearing
Stainless steel roller bearing

mm	mm	kg	mm	mm	mm	mm	mm			
100	35	300	128	100x84	80x60	9	42	HS100.B14.100	HS110.B14.100	HS120.B14.100
125	45	700	164	132x110	105x80	12	61	HS100.B14.125	HS110.B14.125	HS120.B14.125
150	45	700	195	132x110	105x80	12	62	HS100.B14.150	HS110.B14.150	HS120.B14.150
200	50	700	242	132x110	105x80	12	61	HS100.B14.200	HS110.B14.200	HS120.B14.200

Available alternative: Plain bearing

Tread
Plastic

Wheel body
Plastic

Bearing
Stainless steel roller bearing

Bakery castors

Description
Fork of stainless steel
dual-row ball bearings collar in fork head

Model
- Swivel castor
- Fixed castor
- Swivel castor with total brake

mm	mm	kg	mm	mm	mm	mm	mm			
100	35	130	127	95x80	80x60	9	32	H100.B22.100	H110.B22.100	H120.B22.100

INOX

80 - 130 kg

Tread
Phenolic resin,
-40°C/+280°C
short term to +300°C

Wheel body
Phenolic resin

Bearing
Plain bearing

mm	mm	kg	mm	mm	mm	mm	mm			
100	35	130	127	95x80	80x60	9	32	H100.B23.100	H110.B23.100	H120.B23.100

Tread
Thermoplastic blend,
-40°C/+350°C,
short term to +400°C

Wheel body
Thermoplastic blend

Bearing
Plain bearing

mm	mm	kg	mm	mm	mm	mm	mm			
100	30	130	127	95x80	80x60	9	32	H100.B20.101	H110.B20.101	H120.B20.101

Tread
Thermoplastic blend,
black, -40°C/+270°C

Wheel body
Thermoplastic blend

Bearing
Plain bearing

mm	mm	kg	mm	mm	mm	mm	mm			
100	26	80	127	95x80	80x60	9	32	H100.B21.101	H110.B21.101	H120.B21.101

Tread
Red rubber,
-40 °C/+270 °C

Wheel body
Plastic

Bearing
Plain bearing

mm	mm	kg	mm	mm	mm	mm	mm			
100	35	100	127	95x80	80x60	9	32	H100.B24.100	H110.B24.100	

Tread
Blue rubber,
-40°C/+250°C

Wheel body
Aluminium

Bearing
Ball bearing

Bakery castors

Description
Sheet steel fork
zinc-chromatised
dual-row ball bearings collar in fork head

Model
- Swivel castor
- Fixed castor
- Swivel castor with total brake

80 - 150 kg

mm	mm	kg	mm	mm	mm	mm	mm			
100	35	150	126	104x80	84x64/76x56	9	34	L400.B22.100	L410.B22.100	L420.B22.100
100	35	150	126	104x80	84x64/76x56	9	34	L400.B23.100	L410.B23.100	L420.B23.100
100	30	150	126	104x80	84x64/76x56	9	34	L400.B20.101	L410.B20.101	L420.B20.101
100	26	80	126	104x80	84x64/76x56	9	34	L400.B21.101	L410.B21.101	L420.B21.101
100	35	100	126	104x80	84x64/76x56	9	34	L400.B24.100	L410.B24.100	

Tread
Phenolic resin,
-40°C/+280°C
short term to +300°C

Wheel body
Phenolic resin

Bearing
Plain bearing

Tread
Thermoplastic blend,
-40°C/+350°C,
short term to +400°C

Wheel body
Thermoplastic blend

Bearing
Plain bearing

Tread
Thermoplastic blend,
black, -40°C/+270°C

Wheel body
Thermoplastic blend

Bearing
Plain bearing

Tread
Red rubber,
-40 °C/+270 °C

Wheel body
Plastic

Bearing
Plain bearing

Tread
Blue rubber,
-40°C/+250°C

Wheel body
Aluminium

Bearing
Ball bearing