BS ROLLEN®
we are moving everything

Description
Fork of stainless steel
dual-row ball bearings collar in fork head

Model
· Swivel castor
· Fixed castor
· Swivel castor with total brake

INOX

80 - 130 kg

mm	mm	kg	mm	mm	mm	mm	mm			
100	35	130	127	95x80	80x60	9	32	H100.B22.100	H110.B22.100	H120.B22.100
100	35	130	127	95x80	80x60	9	32	H100.B23.100	H110.B23.100	H120.B23.100
100	30	130	127	95x80	80x60	9	32	H100.B20.101	H110.B20.101	H120.B20.101
100	26	80	127	95x80	80x60	9	32	H100.B21.101	H110.B21.101	H120.B21.101
100	35	100	127	95x80	80x60	9	32	H100.B24.100	H110.B24.100	

Tread
Phenolic resin,
-40°C/+280°C
short term to +300°C

Wheel body
Phenolic resin

Bearing
Plain bearing

Tread
Thermoplastic blend,
-40°C/+350°C,
short term to +400°C

Wheel body
Thermoplastic blend

Bearing
Plain bearing

Tread
Thermoplastic blend,
black, -40°C/+270°C

Wheel body
Thermoplastic blend

Bearing
Plain bearing

Tread
Red rubber,
-40 °C/+270 °C

Wheel body
Plastic

Bearing
Plain bearing

Tread
Blue rubber,
-40°C/+250°C

Wheel body
Aluminium

Bearing
Ball bearing

Description
Sheet steel fork
zinc-chromatised
dual-row ball bearings collar in fork head

Model
· Swivel castor
· Fixed castor
· Swivel castor with total brake

80 - 150 kg

mm	mm	kg	mm	mm	mm	mm	mm			
100	35	150	126	104x80	84x64/76x56	9	34	L400.B22.100	L410.B22.100	L420.B22.100
100	35	150	126	104x80	84x64/76x56	9	34	L400.B23.100	L410.B23.100	L420.B23.100
100	30	150	126	104x80	84x64/76x56	9	34	L400.B20.101	L410.B20.101	L420.B20.101
100	26	80	126	104x80	84x64/76x56	9	34	L400.B21.101	L410.B21.101	L420.B21.101
100	35	100	126	104x80	84x64/76x56	9	34	L400.B24.100	L410.B24.100	

Tread
Phenolic resin,
-40°C/+280°C
short term to +300°C

Wheel body
Phenolic resin

Bearing
Plain bearing

Tread
Thermoplastic blend,
-40°C/+350°C,
short term to +400°C

Wheel body
Thermoplastic blend

Bearing
Plain bearing

Tread
Thermoplastic blend,
black, -40°C/+270°C

Wheel body
Thermoplastic blend

Bearing
Plain bearing

Tread
Red rubber,
-40 °C/+270 °C

Wheel body
Plastic

Bearing
Plain bearing

Tread
Blue rubber,
-40°C/+250°C

Wheel body
Aluminium

Bearing
Ball bearing